




**Weasler®**

**RECOMMENDED CUSTOMER LUBRICATION PROCEDURE  
FOR 80° CV DRIVELINES**



LUBRICATE ALL FITTINGS WITH A GOOD CV QUALITY LITHIUM SOAP COMPATIBLE E.P. GREASE MEETING THE N.L.G.I. #2 SPECIFICATIONS AND CONTAINING NO MORE THAN 1% MOLYBDENUM DISULFIDE.

AN E.P. GREASE MEETING THE N.L.G.I. #2 SPECIFICATIONS AND CONTAINING 3% MOLYBDENUM DISULFIDE MAY BE SUBSTITUTED IN THE TELESCOPING MEMBERS ONLY.

LOCATION	STANDARD INTERVAL	EXTENDED LUBE INTERVAL	LEVER ACTION PUMPS
CROSS & BEARINGS	*8 HRS.	50 HRS.	2-3
TELESCOPING MEMBERS	8 HRS.	50 HRS.	8-10
CV BALL & SOCKET	*8 HRS.	50 HRS.	4-6
CV CENTER HOUSING	24 HRS.	50 HRS.	12-15
CE & NON-ROTATING GUARD BUSHINGS (1000 RPM MAX.)	8 HRS.	50 HRS.	2

ROTATING GUARD BUSHINGS SHOULD BE LUBRICATED UPON REPLACEMENT

\*CONSTANT ANGLE APPLICATIONS MAY REQUIRE A LUBE INTERVAL OF 4 HOURS

**CAUTION!! REPLACEMENT PARTS ARE NOT LUBRICATED**

*REPLACEMENT PARTS MUST BE LUBRICATED AT TIME OF ASSEMBLY AND DURING USE PER THE LUBE RECOMMENDATIONS*

**Weasler Engineering, Inc.**  
P.O. Box 558, West Bend, WI 53095 USA  
Tel: +1-262.338.2161, Fax: +1-262.338.3709  
E-mail: oemsales@weasler.com  
web site: www.weasler.com

**Weasler Engineering BV**  
P.O. Box 266, 6600 AG, Wijchen, The Netherlands  
Tel: +31-24-64 89 100, Fax: +31-24-64 89 109  
E-mail: sales@weasler.nl  
web site: www.weasler.nl

**Weasler Engineering Kft**  
P.O. Box 262, H6001, Kecskemet, Hungary  
Tel: +36-76-500410, Fax: +36-76-500 415  
E-mail: sales@weasler.hu