

VRS TORSIONAL DAMPER

Weasler®



Weasler® VRS torsional dampers are designed to provide significant reduction of vibration in many types of powertrain systems, protecting engine and transmission components from excessive wear. By reducing torsional vibration, component life is increased while providing for greater operator comfort and reduced fatigue.

These dampers are desirable for off-road, marine, agricultural, lawn & turf or any engine driven application where cost effective torsional damping and vibration eliminating solutions are needed.

PERFORMANCE BENEFITS

VRS (VISCOUS-RUBBER-SPRING) 3-STAGE TORSIONAL DAMPER (PATENT PENDING)

- **VISCOUS:** GREASE WITHIN THE SPRING POCKETS ELIMINATES TRANSMISSION NOISE DURING IDLE
- **RUBBER:** RUBBER DAMPER REDUCES TORSIONAL FORCES THAT CONTRIBUTE TO GEAR NOISE AND WEAR IN THE TRANSMISSION WHEN OPERATING IN THE FORWARD OR REVERSE POSITIONS AT LOW SPEED
- **SPRING:** COMPRESSION SPRING DAMPENS OUT THE IMPACT AND SHOCK LOADING CREATED DURING NORMAL OPERATION

VRS TORSIONAL DAMPER FEATURES & BENEFITS

- SEALED FOR LIFE TO KEEP GREASE IN AND CONTAMINANTS OUT
- SELF-ALIGNING HUB HELPS ELIMINATE CONCENTRICITY CONCERNS
- BLACK PAINT (OPTIONAL) TO REDUCE RUST AND FOR LONGER STORAGE CAPABILITY
- LOW FRICTION INTERNAL COMPONENTS REDUCE WEAR
- A WIDE VARIETY OF SAE AND METRIC SPLINES AVAILABLE
- TORSIONAL STIFFNESS UP TO 600 FT-LBS OF TORQUE CAPACITY AVAILABLE
- MULTIPLE MOUNTING PATTERNS CAN BE DESIGNED INTO A SINGLE MOUNTING DISC
- DIFFERENT FLYWHEEL CONFIGURATIONS CAN BE ACCOMMODATED

DESIGNED TO MEET YOUR APPLICATION

WEASLER® TORSIONAL DAMPER DESIGNS ARE LIGHTWEIGHT YET ROBUST, PROVIDING THE TORQUE CAPACITY THAT THE APPLICATION REQUIRES. LOW COST AND A HIGH LEVEL OF PERFORMANCE MAXIMIZES THE TORSIONAL DAMPER VALUE. TORSIONAL DAMPER DESIGNS ARE AVAILABLE AS ONE, TWO OR THREE STAGE (VRS), AND ARE SPECIFICALLY DESIGNED TO MEET YOUR PROJECT NEEDS. TO DETERMINE IF YOU CAN BENEFIT FROM THE USE OF THESE PRODUCTS CONTACT OUR DESIGN TEAM ([OEMapplications@weasler.com](mailto: OEMapplications@weasler.com)) AND LET THEM WORK WITH YOU TO IDENTIFY THE PRODUCT TO FIT YOUR SPECIFIC APPLICATION.

APPLICATION DATA SHEET

Weasler®

I. GENERAL

COMPANY			E-MAIL	
ADDRESS			PHONE	
CONTACT	TITLE/DEPT		FAX	

II. APPLICATION


MACHINE/MODEL		PROJECT #		NEW <input type="checkbox"/> EXISTING <input type="checkbox"/> REDESIGN <input type="checkbox"/>
ENGINE MAKE/MODEL		RATED HP		GAS <input type="checkbox"/> DIESEL <input type="checkbox"/>
TRANSMISSION MAKE		MODEL		TYPE
DAMPER MAKE		MODEL		CUSTOMER PART #
ANNUAL USAGE		QTY PER RELEASE		

III. TORSIONAL DAMPER REQUIREMENTS

OPERATING TORQUE (FT•LBF [N•m])		PEAK TORQUE (FT•LBF [N•m])	
MAX RPM		MAX MISALIGNMENT (°)	
THRUST LOAD (LBF [N])		OVERHUNG LOAD (LBF [N])	

IV. GEOMETRY

A	OUTSIDE DISC DIAMETER (in [mm])	
B	MOUNTING BOLT CIRCLE (in [mm])	
C	COVER OFFSET - FROM FLYWHEEL SURFACE (in [mm])	
D	HUB OFFSET - FROM FLYWHEEL SURFACE (in [mm])	
E	OVERALL HUB WIDTH (in [mm])	
F	EFFECTIVE SPLINE LENGTH (in [mm])	
G	HUB SPECIFICATION	
H	NUMBER OF MOUNTING BOLTS	
	MOUNTING BOLT SIZE	



ADDITIONAL DESIGN SPECIFICATIONS (Mounting Pattern, Flywheel Attachment, Duty Cycle, Req'd Life, etc.)

V. SPECIAL REQUIREMENTS: (ie: Delivery, Post-Delivery, Regulatory, Statutory, Other)

NONE <input type="checkbox"/>	
COMPLETED BY:	

*SEND TO WEASLER® OEM APPLICATIONS OR E-MAIL TO: oemapplications@weasler.com

Weasler Engineering, Inc.
P.O. Box 558, West Bend, WI 53095 USA
Tel: +1-262.338.2161, fax: +1-262.338.3709
E-mail: oemsales@weasler.com
web site: www.weasler.com

Weasler Engineering BV
P.O. Box 266, 6600 AG, Wijchen, The Netherlands
Tel: +31-24-64 89 100, fax: +31-24-64 89 109
E-mail: sales@weasler.nl
web site: www.weasler.nl

Weasler Engineering Kft
P.O. Box 262, H6001, Kecskemet, Hungary
Tel: +36-76-500410, fax: +36-76-500 415
E-mail: sales@weasler.hu